

Compact flange ball valve, article 437-GS with lever

Diameter DN 15 up to DN 150

Compact flange-ball valve in economical construction, for general, simple industrial use. Design as 1-part housing with screw-in part. Pressure class depends on nominal diameter up to PN 40. Full bore, floating ball, both sides 100% tight closing. Shaft seal consisting of multilayer PTFE V-rings, preloaded and self-adjusting by belleville washers and additional FKM O-ring.

Suitable for gaseous and liquid media (no steam) considering material resistance cast steel GP240GH.


- **both sides flange connection according to DIN EN 1092-1, pressure range PN 16/PN 40, from diameter DN 65 PN 16**
- **flange with threaded hole according to DIN standard (metric)**
- **ball above with pressure compensation bore**
- **ISO 5211 mounting flange for actuators (direct mounting)**

Operation optionally with lever (lockable), pneumatic or electrical actuator. Unit (ball valve / actuator) is mounted ready for connection including functional test.



	TÜV TA-Luft certified
	Antistatic design 2014/34/EU (Ex II 2 G/D Ex-c II)
	0035
	ambient -20° C ... +60° C
	medium -10° C ... +200° C

Pos.	description	material
1	body / screw-in part	cast steel 1.6019 (GP240GH) with epoxy coating
2	ball	stainless steel 1.4308
3	stem	stainless steel 1.4301
4	ball seal	PTFE-profile shells (TFM 1600)
5	body seal	PTFE
6	stem seal	PTFE
7	O-Ring	FKM (Viton)
8	chevron packing set	PTFE
9	thrust ring	stainless steel 1.4301
10	belleville washers	stainless steel 1.4310
11	stem nut	V2A
12	safety cap	V2A
13	locking device	stainless steel 1.4310
14	lever	stainless steel 1.4310



Compact flange ball valve, article 437-GS with lever

Diameter DN 15 up to DN 150

- Design Standard DIN EN 12516-1
- Housing strength DIN EN 12516-2
- Design pressure PN 68 / PN 63 / PN 50 (depending on nominal diameter)
- Identification EN 19, MSS SP-25
- Inspection / test DIN EN 12266 P10 / P11 / P12
- Housing cast AD 2000-data sheet W0 (TÜV)




shaft sealing according to VDI 2440 (TA-Luft)

Operating stem is inserted into the body shaft from inside. This guarantees blow-out safety stem.

ATEX-antistatic, the ball-stem connection and the stem-body connection have a anti static feature, which ensures electrical continuity contact between those parts. As a result the ball valve complies with the ATEX Directive 2014/34/EU (Ex II 2 G/D Ex-c II)

The highly polished solid ball has a **pressure relief hole** in the stem slot in order to avoid pressure build-up in the body cavity. This ensures a right shutoff and a long service life




Disc springs ensure the permanent pretensioning of the chevron ring set.

primary shaft seal 3-ply V-ring chevron packing set (PTFE)

secondary shaft seal (O-ring FPM)

tertiary shaft feedthrough (PTFE sealing washer)



Operating-variants:

pneumatic



electrical




electrical



Compact flange ball valve, article 437-GS with lever

Diameter DN 15 up to DN 150




	Article-No.													
Diameter	437-GS Cast steel 1.0619	L (mm)	H (mm)	H1 (mm)	d (mm)	C / W (mm)	LK (mm)	n x M	S1/S2	VK (mm)	T1 (mm)	T2 (mm)	Pressure rating max. (bar)	Weight (kg)
DN 15	215.3868.4.11	42	77	49	15,0	145	65	4 x M12	F03/F04	9	4x6	4x6	40	1,4
DN 20	215.3868.4.13	44	82	55	20,0	145	75	4 x M12	F03/F04	9	4x6	4x6	40	1,8
DN 25	215.3868.4.15	50	94	62	25,0	175	85	4 x M12	F04/F05	11	4x6	4x7	40	2,4
DN 32	215.3868.4.18	60	104	72	32,0	175	100	4 x M16	F04/F05	11	4x6	4x7	40	3,9
DN 40	215.3868.4.19	65	114	78	38,0	194	110	4 x M16	F05/F07	14	4x7	4x9	40	4,9
DN 50	215.3868.4.21	80	120	86	50,0	194	125	4 x M16	F05/F07	14	4x7	4x9	40	8,6
DN 65	215.3868.4.24	110	158	108	63,5	265	145	4 x M16	F07/F10	17	4x9	4x11	16	10,1
DN 80	215.3868.4.25	120	165	116	76,0	265	160	8 x M16	F07/F10	17	4x9	4x11	16	14,5
DN 100	215.3868.4.27	150	182	139	95,0	400	180	8 x M16	F10	22	-	4x11	16	22,7
DN 125	215.3868.4.28	180	224	176	118,0	600	210	8 x M16	F12	27	-	4x14	16	50,0
DN 150	215.3868.4.29	225	268	192	142,0	800	240	8 x M20	F12	27	-	4x14	16	70,0

Diameter	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 125	DN 150
Ø	15,0	20,0	25,0	32,0	38,0	50,0	63,5	76,0	95,0	118,0	142,0
KV	15,5	31,0	41,3	80,0	141,9	178,2	387,0	670,8	1.169,6	1.456,9	2.228,20


Compact flange ball valve, article 437-GS with optional accessories

Diameter DN 15 up to DN 150

optional accessories consoles / couplings / shaft extensions



ISO 5211 consoles
Steel zinc plated / stainless steel



couplings stainless steel
Square / two-flat




shaft extension ISO 5211
100 mm stainless steel



shaft extension T-handle
100 mm stainless steel

optional accessories limit switch assembly with box or open mounted

limit switch box 2-fold Honeywell, ZM1



switching capacity	max. 5 A, 250 V AC
temperature range	-25° C up to +85° C
cable entry	M20 x 1,5
connection	clamp 2,5 mm ²
body material	aluminium
console	stainless steel
article-no:	179.8705HEZ

mounting kit for switch boxes incl. assembly and adjustment



diameter (ball valve)	article-no:
1/4" ... 1/2"	327.8775.F04VMM
3/4" ... 1"	327.8775.F05VMM
1 1/4" ... 2"	327.8775.F07VMM
2 1/2" ... 4"	327.8775.F10VMM

Bernstein-limit switches type I88-SU1Z RiW K




1-fold




2-fold

switching capacity	max. 10 A, 250V AC
temperature range	-30° C up to +80° C
cable entry	M20 x 1,5
connection	clamp 2,5 mm ²
body material	PA 6 self-extinguishing
article-no:	1-fold: 208.8716HKE 2-fold: 208.8716HKZ

IFM proximity switches type IF5297




1-fold




2-fold

operating voltage	10 ... 55 V DC
current consumpt.	< 15 mA (24 V)
temperature range	-25° C up to +80° C
body material	brass with LED
mounting bracketed	stainless steel / plastic
article-no:	1-fold: 302.8770HEE 2-fold: 302.8770HEZ

IFM proximity switches type IFS209



1-fold



2-fold

operating voltage	10 ... 30 V DC
current consumpt.	< 12 mA (24 V)
temperature range	-25° C up to +70° C
body material	brass with LED
mounting bracketed	stainless steel / plastic
article-no:	1-fold: 302.8771HEE 2-fold: 302.8771HEZ